

## VERSION WITH MARKINGS TO SHOW CHANGES MADE TO CLAIMS

BEST ANAILABLE COPY

2	<u>I claim</u> :
3	A body supporting, serial inflating seat, com
4	a. at least three transversely aligned, in
5	b. an air pump connected to each said a
6	bladders;
7	c. a valve means connected to each said
8	and out of each said air bladder;
9	d. a timer connected to said pump to se
10	front to back, and connected to said valve means to
11	a pre-selected time period; and,
12	e. a transversely aligned, rear cushion d
13	bladder for continuously supporting the ischial tuber
14	
15	2. The body supporting, serial inflating seat, as
16	control switch connected to said valve means that en
17	constantly inflated, constantly deflated, or sequential
18	
19	3. The body supporting, serial inflating seat, co
20	a. two sets of three transversely aligned
21	b. an air pump connected to each set of

## **CLAIMS**

nprising:

1

- ıflatable air bladders;
- air bladder to selectively inflate said air
- d air bladder to control the flow of air into
- equentially inflate said air bladders from sequentially deflate said air bladders after
- lisposed adjacent to the rear-most said air rocities of the user when sitting.
- recited in Claim 1, further including a nables one of the said air bladders to be ally inflated and deflated.
- omprising:
  - l, inflatable air bladders;
- said air bladder to selectively inflate said air bladders;

•	-	
2		
3		
4		
5		
6		
7		
8		
9	1	
10	1	
11		
12		
13		
14		
15		
16		
17		
18		
19		
20		
21		
22		
23		

c.	a valve means connected to each said air bladder to control the flow of air into
and out of eac	h said air bladder;

- d. a timer connected to said pumps and said valve means to sequentially inflate and deflate said air bladders after a pre-selected time period; and,
- e. a transversely aligned, rear cushion disposed adjacent to the rear-most said air bladder for continuously supporting the ischial tuberocities of the user when sitting.

3.4. The body supporting, serial inflating seat, as recited in Claim 3, further including a control switch connected to said valve that enables said air bladders in one set of said air bladders to be constantly inflated, constantly deflated, or sequentially inflated and deflated.